(12) UK Patent Application (19) GB (11) 2 377 427 (13) A

(43) Date of Printing by UK Office 15.01.2003

- (21) Application No 0222898.9
- (22) Date of Filing 19.12.2001
- (30) Priority Data
 - (31) 0031627
- (32) 23.12.2000
- (33) GB
- (86) International Application Data
 PCT/GB2001/005649 En 19.12.2001
- (87) International Publication Data W02002/051739 En 04.07.2002
- (71) Applicant(s)

 EBAC Limited
 (Incorporated in the United Kingdom)
 St Helen Trading Estate,
 BISHOP AUCKLAND, Co Durham,

DL14 9AL, United Kingdom


(72) Inventor(s)
Philip Andrew Walton
Gary Squire
Robert Tansley
Andrew Gibbs

- (51) INT CL⁷ B67D 1/00
- (52) UK CL (Edition V)

 88N NB NJE N24C1 N24C2B N24D7 N24E3 N24E5
 N24E7
- (56) Documents Cited by ISA
 None
- (58) Field of Search by ISA Other: NOT YET ADVISED
- (74) Agent and/or Address for Service
 Craske & Co
 Patent Law Chambers, 15 Queens Terrace,
 EXETER, Davon, EX4 4HJ, United Kingdom

(54) Abstract Title Gassed liquid dispensers

(57) Water supplied from a bottle 1 is pre-chilled in a reservoir 3. A two-part water pump 11 transfers water under pressure through a jet nozzle 14 into an oxygen space 17 in a PET pressure vessel 12, which entrains oxygen into the water. The pressure vessel is received in a conductive holder 18 and is cooled by a peltier element 19 provided with cooling fins 20. The holder 18 forms a capacitive level sensor with a probe 32 inside the vessel, which starts the pump 11 when oxygenated water is drawn off via a draw tube 28 and discharge valve 31. When the water level in the oxygenating vessel is restored a solenoid valve 25 opens to restore the oxygen pressure in the vessel. For hygiene purposes the pumping body can be removed from the pump motor and replaced together with the reservoir 3 and oxygenating vessel 12 along with the associated tubing.



GB 2377427

Oxygenating water cooler	
Patent Number:	☐ <u>GB2370561</u>
Publication date:	2002-07-03
Inventor(s):	SQUIRE GARY (GB); GIBBS ANDREW (GB); TANSLEY ROBERT (GB); WALTON PHILIP ANDREW (GB)
Applicant(s):	EBAC LTD (GB)
Requested Patent:	☑ <u>GB2377427</u>
Application Number:	GB20000031627 20001223
Priority Number(s):	GB20000031627 20001223
IPC Classification:	B67D1/00
EC Classification:	B67D1/00E4, B67D1/00H4
Equivalents:	☐ <u>WO02051739</u>
Abstract	
Water supplied from a bottle 1 is pre-chilled in a reservoir 3. A two-pad water pump 11 transfers water under pressure through a jet nozzle 14 into an oxygen space 17 in a PET pressure vessel 12, which entrains oxygen into the water. The pressure vessel is received in a conductive holder 18 and is cooled by a peltier element 19 provided with cooling fins 20. The holder 18 forms a capacitive level sensor with a probe 32 inside the vessel, which starts the pump 11 when oxygenated water is drawn off via a draw tube 28 and discharge valve 31. When the water level in the oxygenating vessel is restored a solenoid valve 25 opens to restore the oxygen pressure in the vessel. For hygiene purposes the pumping body can be removed from the pump motor and replaced together with the reservoir 3 and oxygenating vessel 12 along with the associated tubing.	
Data supplied from the esp@cenet database - I2	